



duoPower Havalı Soğutucular duoPower Air Heat Exchangers	$\Delta t=20\text{ }^{\circ}\text{C}$ 'de soğutma kcal/saat Cooling kcal/hr	$\Delta t=30\text{ }^{\circ}\text{C}$ 'de kcal/saat kcal/hr	Maks Yağ debisi litre/dak Max. oil lt./mn	Maks.Basınç Bar Max. pressure bar	Yağ bağlantı Ölçüsü Oil connection dia.
4010 TK 24V DC	940	1400	40	24	1/2" BSP
4010 TK 220V AC	940	1400	40	24	1/2" BSP
4015 TK 24V DC	2330	4100	80	24	1" BSP
4015 TK 220V AC	2330	4100	80	24	1" BSP
4020 TK 24V DC	3020	4520	100	24	1" BSP
4020 TK 220V AC	3020	4520	100	24	1" BSP
4024 TK 24V DC	5670	8470	120	24	1" BSP
4024 TK 220V AC	5670	8470	120	24	1" BSP
4024 TK 230-400 AC 3 FAZ	5670	8470	120	24	1" BSP
4030 TK 24V DC	7880	12030	140	24	1" BSP
4030 TK 220V AC	7880	12030	140	24	1" BSP
4030 TK 230-400 AC 3 FAZ	7880	12030	140	24	1" BSP
4040 TK 24V DC	10050	15030	160	24	1 1/4" BSP
4040 TK 220V AC	10050	15030	160	24	1 1/4" BSP
4040 TK 230-400 AC 3 FAZ	10050	15030	160	24	1 1/4" BSP
4050 TK 24V DC 4 FANLI	13550	20050	180	24	1 1/4" BSP
4050 TK 220V AC	13550	20050	180	24	1 1/4" BSP
4050 TK 230-400 AC 3 FAZ	13550	20050	180	24	1 1/4" BSP
4030 2TKS ÇİFT FANLI 24V DC	15550	23500	260	24	1 1/4" BSP
4030 2TKS ÇİFT FANLI 220V AC	15550	23500	260	24	1 1/4" BSP
4040 2TKS ÇİFT FANLI 24V DC	19400	29400	320	24	1 1/2" BSP
4040 2TKS ÇİFT FANLI 220V AC	19400	29400	320	24	1 1/2" BSP
TK 6 (230/400 3 FAZ 0.55KW 1500 D/D	26100	35100	200	26	1 1/4" BSP
TK 8 (230/400 3 FAZ 2.2KW 1500 D/D	51100	72050	250	26	1 1/2" BSP
TK 10 (230/400 3 FAZ 5.5KW 1500 D/D	135100	180100	500	10	SAE 3"